


Precision Studiophones

ATH-M40fs Flat response

ATH-D40fs Bass enhanced



 **audio-technica.**

Precision Studiophones

Two field-serviceable models featuring application-specific performance

ATH-M40fs and ATH-D40fs Precision Studiophones deliver premium performance, coupled with long-lasting reliability and comfort, for specialized uses.

Two Custom-tailored Designs

The ATH-M40fs is designed specifically for professional monitoring/mixing, with a flat, extended low-frequency response to 5 Hz, that ensures accurate sound reproduction.

The ATH-D40fs features an enhanced bottom-end response (from around 20 Hz to 500 Hz), making them ideal for use with predominantly low-frequency sound sources such as bass instruments and drums.

Superior Performance

Built for power and precision with large 40mm diameter drivers, neodymium magnets and CCAW (copper-clad aluminum wire)

voice coils, A-T Precision Studiophones deliver 1,600 mW of power handling and very high SPL capability while maintaining exceptional clarity and accuracy of sound throughout their extended ranges.

Durability, Comfort, Convenience

Both models have adjustable padded headbands and sturdy, ultra-flexible strain-relief cables made of OFC litz wire, with convenient one-side exit. Comfortable circumaural earpieces provide maximum isolation, and can be rotated 180° to permit one-ear monitoring. Plus, replacement elements, cables and ear pads are available for quick, easy repair in the field.

Successfully integrating superior design, materials and craftsmanship, Audio-Technica Precision Studiophones represent a new standard in studio monitoring excellence.

ATH-M40fs Flat response



Specifications

Type: Closed-back dynamic

Driver diameter: 40 mm

Magnet: Neodymium

Voice coil: Copper-clad aluminum wire

Frequency response: 5-20,000 Hz

Maximum input power: 1,600 mW at 1 kHz

Sensitivity: 100 dB

Impedance: 60 ohms

Weight: 8.8 oz (250 g) without cable

Cable: 11' (3.4 m) (OFC litz wire, left-side exit)

Connector: 1/4" (6.3 mm) phone plug

ATH-D40fs Bass enhanced



Specifications

Type: Closed-back dynamic

Driver diameter: 40 mm

Magnet: Neodymium

Voice coil: Copper-clad aluminum wire

Frequency response: 20-20,000 Hz

Maximum input power: 1,600 mW at 1 kHz

Sensitivity: 102 dB

Impedance: 66 ohms

Weight: 8.8 oz (250 g) without cable

Cable: 11' (3.4 m) (OFC litz wire, left-side exit)

Connector: 1/4" (6.3 mm) phone plug



audio-technica.

Audio-Technica U.S., Inc., 1221 Commerce Drive, Stow, Ohio 44224 330/686-2600 Fax: 330/686-0719

Audio-Technica Limited, Old Lane, Leeds LS11 8AG England 0113 277 1441 Fax: 0113 270 4836

Form No. 0205-0630-01 ©1997 Audio-Technica U.S., Inc. Printed in U.S.A.