

ATH-M30 Professional Monitor Headphones



Closed-back dynamic stereo headphones deliver exceptional clarity

Sonic accuracy for mixing with high power handling for tracking sessions

40 mm drivers with neodymium magnets and CCAW voice coils

Circumaural design ensures superior isolation

Adjustable cushioned headband and light weight provide maximum comfort

Gold-plated stereo $^{1\!/_{8}"}$ (3.5 mm) connector with strain relief and professional screw-on $^{1\!/_{4}"}$ (6.3 mm) adapter

Sturdy, ultra-flexible, OFC litz wire cable with single-side exit

ATH-M30 Specifications

ТҮРЕ	Closed-back dynamic
DRIVER SIZE	40 mm diameter
MAGNET	Neodymium
VOICE COIL	Copper-clad aluminum wire
FREQUENCY RESPONSE	20-20,000 Hz
MAXIMUM INPUT POWER	1,600 mW at 1 kHz
SENSITIVITY	100 dB
IMPEDANCE	65 ohms
WEIGHT	7.0 oz (200 g) without cable
CABLE	11' (3.4 m), OFC litz wire, left-side exit
CONNECTOR	$^{\prime}\!\!/\!\!s^{*}$ (3.5 mm) with screw-on $^{\prime}\!/\!\!4^{*}$ (6.3 mm) adapter







Audio-Technica U.S., Inc., 1221 Commerce Drive, Stow, Ohio 44224 (330) 686-2600 Fax: (330) 686-0719 E-mail: pro@atus.com www.audio-technica.com Audio-Technica Limited, Old Lane, Leeds LS11 8AG England (0) 113 277 1441 Fax: (0) 113 270 4836 E-mail: sales@audio-technica.co.uk

