

Bugera

THE SOUL OF VALVES

333-212
Specifications

BUGERA 333-212

Boutique-Style 120-Watt 3-Channel Valve Combo with Reverb

- ◆ Hand-built 120-Watt guitar combo driven by 4 x 6L6 valves (convertible to EL34)
- ◆ 2 original heavy-duty 12" BUGERA guitar speakers for true vintage sound
- ◆ Classic 3-channel preamp design (Clean, Crunch, Lead) featuring 4 x 12AX7 valves for terrifying punch and mind-blowing gain
- ◆ Integrated high-class reverb with dedicated Reverb control
- ◆ Independent Equalizer sections for each channel with dedicated Bass, Mid and Treble control
- ◆ Damping switch (High, Medium, Low) for total sound control
- ◆ Impedance switch (4, 8 and 16 Ohms) to match virtually any speaker cabinet
- ◆ FX Loop with independent Send and Return level controls also serves as Boost function
- ◆ Heavy-duty footswitch for Channel selection and FX Loop/Boost function included
- ◆ Line output with dedicated Level control
- ◆ High-quality components and exceptionally rugged construction ensure long life

Specifications

PREAMP SECTION

Valves	
Type	2 x 12AX7A 2 x 12AX7
Preamp high-gain input	
Impedance	470 k Ω
Clean channel	
Nominal input level	-20 dBV
Min. input level	-30 dBV
Max. input level	0 dBV
Crunch channel	
Nominal input level	-80 dBV
Min. input level	-90 dBV
Lead channel	
Nominal input level	-80 dBV
Min. input level	-90 dBV
Effects send	
Impedance	47 k Ω or higher
Min. output level	-10 dBV, 300 mV RMS
Max. output level	0 dBV, 1 V RMS
Effects return	
Impedance	470 k Ω
Min. input sensitivity	-10 dBV
Max. input sensitivity	0 dBV
Line output	
Impedance	47 k Ω or higher
Adjustable output level	\pm 20 dBV

POWER AMPLIFIER SECTION

Valves	
Type	4 x 6L6GC
Output power	
Peak power	120 W / 16, 8, 4 Ω
Loudspeaker connectors	
Type	¼" mono jack connectors, unbalanced
Load impedance	4 Ω / 8 Ω / 16 Ω switchable
Internal loudspeakers	
Type	2 x 12" BUGERA, 12G70J8
Impedance	8 Ω
Continuous power	70 W (IEC)
Total impedance	16 Ω (series connection)

POWER SUPPLY

Power consumption	Max. 350 W
Fuse	T 3.15 A H 250 V (100 – 120 V \sim , 50/60 Hz) T 1.6 A H 250 V (220 – 240 V \sim , 50/60 Hz)
Mains connection	Standard IEC receptacle

DIMENSIONS/WEIGHT

Dimensions (H x W x D)	Approx. 20 13/32" x 27" x 9 3/4" (518.46 mm x 687.3 mm x 247.65 mm)
Weight	Approx. 63 lbs (28.5 kg)

We are constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance are subject to change without notice. The information contained herein is correct at the time of printing. All trademarks (except BUGERA, the BUGERA logo, and THE SOUL OF VALVES) mentioned belong to their respective owners, and such use neither constitutes a claim of the trademarks by RED CHIP COMPANY LTD nor affiliation of the trademark owners with RED CHIP COMPANY LTD. RED CHIP COMPANY LTD accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary slightly from product. Our Products are sold through authorized dealers only. This manual is copyrighted. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of RED CHIP COMPANY LTD. BUGERA-products are distributed exclusively by the BEHRINGER Group of companies globally, and specifically by BEHRINGER International GmbH in the European Union.