C519 M / C519 ML @AK



PROFESSIONAL MINIATURE CLIP-ON CONDENSER MICROPHONE



HIGHLIGHTS

CARDIOID POLAR PATTERN

for problem-free use with high ambient noise rejection

FLEXIBLE SHOCK MOUNT

for efficient suppression of mechanical and body noise

RUGGED, HIGHLY STABLE GOOSE-NECK

for precise placement of the microphone


DETACHABLE MICROPHONE CABLE

easy to install and service

RUBBERIZED MOUNTING CLIP

for firm, gentle fit on a wide variety of instruments

KEY MESSAGES



The MPAV from C519 M features an integrated, switchable bass cut for adjusting the microphone's frequency response. The C519 ML package includes a mini-XLR cable and the unique A400 adapter plate for easy mounting onto wireless body-pack transmitters PT40/45/450/470.

APPLICATIONS

TRUMPET, SAXOPHONE, TROMBONE, TUBA, DIDGERIDOO, OTHER WIND INSTRUMENTS

www.akg.com/pro Issued: 4/2018

C519 M / C519 ML @A



PROFESSIONAL MINIATURE CLIP-ON CONDENSER MICROPHONE

TECHNICAL SPECIFICATIONS ■

AUDIO FREQUENCY BANDWIDTH: 60 - 20000 Hz

EQUIVALENT NOISE LEVEL: 31 dB-A
SENSITIVITY: 5 mV/Pa
SIGNAL TO NOISE: 63 dB-A
ELECTRICAL IMPEDANCE: 2000 Ohms
RECOMMENDED LOAD IMPEDANCE: 2000 Ohms
POLAR PATTERN: Cardioid

POWERING INTERFACE: Voltage: 9 to 52 V

Current: 2 mA

AUDIO OUTPUT: C519 M: 3-pin Mini XLR Female (and

includes MPAV phantom adapter) C519 ML: 3-pin Mini XLR Female (and includes A400 adapter plate)

DESIGN: Body: Metal

Finish: Matte black

DIMENSIONS: Width: 47 mm

Height: 213 mm Net Weight: 195 g



Issued: 4/2018

INCLUDED ACCESSORIES

C519 M

- Mini-to-Standard XLR Cable (3 m/10 ft.)
- W44 Windscreen
- Microphone Bag

C519 ML

- Mini-XLR Cable (1.5 m/5 ft.)
- A400 Adapter Plate
- W44 Windscreen
- Microphone Bag



AKG ACOUSTICS GMBH LAXENBURGER STRASSE 254, 1230 VIENNA/AUSTRIA.

AKG ACOUSTICS, U.S. 8400 BALBOA BOULEVARD, NORTHRIDGE, CA 91329, U.S.A.