

## CX Series Crossovers

Offering a variety of options for virtually all live sound reinforcement amplifier configurations, the CX Series makes state-of-the-art crossover technology affordable.



**CX-22SW** 2-way stereo + subwoofer



**CX-23SW** 3-way stereo + subwoofer



**CX-2213** 2-way stereo + 3-way mono



**CX-2314** 3-way stereo + 4-way mono

- Single rack space (1U), metal housing
- Top audio performance with high slew rate circuitry and over 115dB dynamic range for clear transparent sound
- Designed for the most precise accurate control
- Phase inversion switches
- Low-cut subsonic filters for low frequency driver protection
- Servo-balanced XLR inputs
- Switchable constant directivity horn equalization circuit for use with horns requiring a high frequency boost (CX-2213, CX-2314)
- State-variable Linkwitz Riley 24dB/ octave filters (CX-2213, CX-2314)
- Shielded internal power supply with AC voltage select switch (~115V/60Hz or ~230V/50Hz)

## PCL Series Power Line Conditioners

For advanced RF/EMI noise filtering and the quietest operation of your equipment...



**PCL-800** Power conditioner



**PCL-810** Power conditioner with dimmable front-panel slide-out lights



**PCL-815** Power conditioner with lights and AC meter display

- Triple mode varistor surge and spike protection
- Eight rear outlets (with room for 4 "wall warts") controlled by a front panel switch
- 15 amp rating (1800 W) with rear panel circuit breaker (UL)
- Two added front panel slide-out, swiveling lights for rack illumination and dimmer controls to adjust lamp brightness (PLC-810 and PLC-815 only)
- Large LED numeric meter that displays incoming AC line voltage and 2 voltage condition indicators—standard voltage and over voltage (PLC-815 only)
- Rugged single rack space metal housing for maximum reliability