COLUMN CLAMP MOUNTS

KONTOUR[™] SERIES

FEATURES

HEAVY DUTY DESIGN

Sleek, solidly constructed forged aluminum arms.

2 ULTIMATE FLEXIBILITY

Dynamic height adjustment using gas-spring technology with additional adjustment along the column. Ideal for sit-stand applications.

FAST INSTALLATION

3

Simple 3-step installation and integrated quick-connect interface for easy mounting and maintenance.

CABLE MANAGEMENT

Tool-free cable management covers for a clean, professional look.

CENTRIS[®] EXTREME TILT


PATENTED FEATURE Tilts -75°/+10° for an ultimate ergonomic solution.

SPECIFICATIONS

Depth from Back of Desk	2.13" (54 mm)
Max. Extension	21.7" (551 mm)
Tilt	-75° / +10°
Height Assist (Column + Arm)	20.8" (528 mm)
Weight Capacity*	5–25 lbs (2.3–11.3 kg)
Colors	Black, Silver

* Per monitor

TECHNICAL DRAWINGS





WHAT YOU NEED TO KNOW

INSTALLING THE MONITOR MOUNT The mounting surface thickness must be between 0.5"-3.25" (12-82 mm).

MOUNTING PATTERNS Compatible with 75 x 75 mm and 100 x 100 mm VESA[®] patterns.

QUICK-CONNECT INTERFACE

Easily attach and remove interface from mounting head without removing monitor – no tools necessary!



INSTALLATION

KRA204 Column Clamp Grommet Accessory





