

EUROGRAND EG2080-RW/BK

Technical Specifications

GB

Version 1.0 April 2006



www.behringer.com



EUROGRAND

The Sound, Touch and Elegance of an Acoustic Grand Piano –

The Cutting-Edge Performance of a Digital Piano

GB

- ▲ The ultimate piano for homes, music schools, houses of worship, etc. No traditional tuning or maintenance needed
- ▲ Elegant wood grain cabinet with either black or dark rosewood finish, sliding key cover and full modesty panel
- ▲ 88-note weighted hammer-action keyboard accurately recreates the feel of an acoustic grand piano
- ▲ High-grade 80-Watts speakers and cabinetry deliver a truly dynamic sound, rich with presence and power
- ▲ New stereo sampling RSM (Real Sound Memory) tone generation for the ultimate in instrument realism
- ▲ 14 high-quality voices (Grand Piano, Acoustic Piano, E-Piano, Strings, Harpsichord, Organ, etc.) with max. 64-note polyphony
- ▲ Layer mode for playing 2 sounds together
- ▲ High-quality reverb, modulation and brilliance effects to add even more depth and richness
- ▲ Real-time 2-track song recorder with one song capacity and metronome
- ▲ 3 pedals (Damper, Sostenuto and Soft) for more dynamic playing
- ▲ Comprehensive MIDI In/Out/Thru and stereo line in/out connectors
- ▲ Dual headphone jacks for silent music rehearsal and student/tutor listening
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

EUROGRAND EG2080-RW/BK

EUROGRAND EG2080-RW/BK

SPECIFICATIONS

KEYBOARD	88 weighted keys with hammer action (A-1 to C7)
SOUND GENERATION	RSM (Real Sound Memory) stereo sampling, 32 MB ROM
POLYPHONY	64 notes max.
SOUNDS	14
EFFECTS	
Room effects	4 types (ROOM, HALL 1, HALL 2, STAGE)
Modulation effects	4 types (CHORUS, FLANGER, TREMOLO, DELAY)
SEQUENCER	
Type	2-track
Memory	1 Song, approx. 10,000 notes
PEDALS	3 (soft-, sostenuto-, damper)
LINE IN	
Connectors	1/4" TS jack, unbalanced
Impedance	approx. 10 kΩ
LINE OUT	
Connectors	1/4" TRS jack, impedance-balanced RCA, unbalanced
Impedance	approx. 100 Ω, unbalanced approx. 200 Ω, balanced
Max. output level	+7 dBu
PHONES	
Connectors	1/4" TRS jack
Max. output level	+13 dBu/120mW @ 100 Ω load
MIDI	IN, OUT, THRU
AMPLIFIER	
Output power	2 x 40 W
POWER SUPPLY	
Mains voltages	
USA/Canada	120 V~, 60 Hz
China/Korea	220 V~, 50 Hz
Europe/U.K./Australia	230 V~, 50 Hz
Japan	100 V~, 50 - 60 Hz
Export model	120/230 V~, 50 - 60 Hz
Power consumption	approx. 135 W
Fuse	100 - 120 V~: T 2,5 A, H 250V 220 - 240 V~: T 1,25 A, H 250 V
DIMENSIONS/WEIGHT	
Dimensions (H x W x D)	approx. 880 mm (34 21/32") x 1,405 mm (55 5/16") x 525 mm (20 43/64")
Weight	approx. 67 kg (147.7lbs)

GB

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2006 BEHRINGER Spezielle Studiotechnik GmbH,
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903