



®



FUCHS ODH® HYBRID GUITAR AMPLIFIER

V 1.0

Operations Manual

Fuchs Audio Technology
407 Getty Avenue 2nd Floor
Clifton, N.J. 07015
(973) 772-4420

Website: www.fuchsaudiotechnology.com

Email: techsupport@fuchsaudiotechnology.com

© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs ODH Amp manual Rev. 1.0 01-2024-AMF

A Note from Andy,

First of all, *thank you* for purchasing the new Fuchs ODH hybrid amp !

As an aging guitar player, close to ten years ago, I began to begin a quest to bring tube ODS tones to the lightest and most compact platform I could. The ODH is the result of years of tweaking my own gig rig to make it light and still sound up to the tones of my ODS amps.

Each Fuchs product is precision handmade by myself and the staff at Fuchs Audio, built to extremely high standards of excellence using the highest quality components. With over two decades experience in the service, manufacturing, and design of tube audio/music equipment, we at Fuchs Audio are extremely proud of the quality and tremendous musicality of all our products, and know you'll feel the same way.

Please read this manual carefully. Doing so will allow you full understanding of your amplifier and operation, thus quickly providing you the tones & performance you want. Your Fuchs ODH amp can only perform to its fullest glory by your full understanding of all its features.

Feel free to call or e-mail us with comments & questions about your amp, or just to find out what's new here at Fuchs Audio.

Lastly, I recommend checking out our web site:
www.fuchsaudiotechnology.com, or www.fuchsaudiodirect.com for product/user updates, cool links and other info benefiting our customers.

Sincerely,

Andy Fuchs
President

Fuchs Audio Technology®

Fuchs Audio Technology®	407 Getty Ave Second Floor West
Clifton NJ 07011 (ph) 973-772-4420 (fax) 973-772-4460	info@fuchsaudio.com
www.fuchsaudiotechnology.com	info@fuchsaudiotechnology.com

("Fuchs Audio Technology" ODH is a registered trademarks of Fuchs Audio Technology)

© 2024 Fuchs Audio Technology. All rights reserved.

Instructions for Fuchs ODH Amp:

Table of Contents (by section)

- 1) Introduction to Fuchs Audio Technology Amplifiers
- 2) Please Read before powering up your AMP!
- 3) Diagrams- FRONT/REAR panel controls
- 4) Front panel Controls & their functions
- 5) (A) Rear Panel details
- 6) Effects Loop
- 7) DI Output details.
- 8) Warranty/repair information & mail-in warranty form

1 Introduction to Fuchs Audio Technology Amplifiers

What makes our products unique?

The recent proliferation of "Boutique" guitar amplifiers, allows guitarists to recognize what audiophiles have known for years; properly designed circuits can offer the finest musicality, detail, and sensitivity to playing subtleties of any type amplifier. Anyone who's enjoyed the sweet, responsive character of a well-built boutique amplifier realizes you can't model or computer simulate the "organic" qualities, no matter how hard you try. It's like enjoying fresh food or food that's been frozen. Something gets lost in the translation.

We feel our designs go a few steps beyond those of other manufacturers!

In addition to refining our circuit designs and operating points with computer "Spice" modeling, we also spend countless hours tuning our circuits through careful parts selection and refining the internal layout of our products. Details like single-point star grounding of all internal circuits, premium audiophile grade power and output transformers, high speed switching diode power supplies, regulated and

© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs ODH Amp manual Rev. 1.0 01-2024-AMF

2

Please read before powering up your amp

Please see Panel Diagrams in next section 3 for assistance.

- 1) Make certain a speaker (load) is plugged into the speaker jacks on the back of the amplifier. The amp will drive 2.65 (8 and 4 in parallel, for nearly 500 watts), 4 ohms for 300 watts, and 8 ohms for about 150 watts.
- 2) Reduce all front PANEL controls (MASTER, GAIN) to moderate levels (approx at 7-9 o'clock positions). Set tone controls to 12.00 positions.
- 3) Install instrument cable from guitar into front panel INPUT
- 4) Put mute switch in mute position.
- 5) Install power cord to amplifier (AC POWER IN) and to AC power source.
NOTE: The Fuchs ODH amps are universal AC power devices, which means they will work anywhere in the world and automatically select the proper line voltage automatically.
- 6) POWER UP amplifier by: 1) flipping rear panel POWER rocker switch. These amps have a 30 second mute at turn on to allow the tubes to stabilize. The mute switch is overridden while the amp mute circuit is in mute mode. The solid state models will play immediately, so make sure your levels are low initially.
- 7) The Amplifier is now fully on and ready to use. Feel free to adjust all controls as you see fit.

TO PUT AMP IN MUTE MODE- Simply flip the MUTE switch into mute position.

TO PUT AMP IN PLAY MODE- Simply flip the MUTE switch to on position.

TO TURN AMP OFF Flip the mute switch to mute mode, and switch off the AC power.

Please Note: The Fuchs ODH tube amp uses two premium selected 12AX7 tubes in the clean and dirty channels. The amp uses a 6AL5 dual diode tube as a tube compressor. NEVER remove the tubes during operation and do not apply power until without tubes in place. This can cause damage to power supply components in the amp which are not field serviceable. These tubes should last many years without replacement. Should the amp become noisy, or lose gain or sound, they should be replaced with premium selected preamp tubes.

©© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs Bass Amp manual Rev. 1.0 01-2024-AMF

3 Rear panel details.



4 Front Panel Controls and Their Functions



© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs ODH Amp manual Rev. 1.0 01-2024-AMF

Input Jack:

Input jack is a 1/4" phone plug, designed for 1-Meg impedance, guitar-level signal. This input will readily accept pedals/effects without any loss in performance. The design of our ODH amps are quite flexible, so we first suggest exploring its performance without any effects or pedals initially.

Input Gain Control:

The gain control sets the input gain for the amplifier. The gain control sets the preamp gain. Lower settings for active pickups, higher settings for passive pickups. Depending on the instrument, running the gain control high and master volume low can give you distortion (whether you desire that is up to you). Running the gain low and master high will result in the maximum cleanest signal from the amp.

High Control:

The High control boosts and cuts high frequencies. The high control operation is shifted down into the midrange by the two-position mid boost switch. Center position is "normal" and the two additional positions offer two different mid boosts at different frequencies, allowing you to tailor the tone to your goal and guitars, speakers, etc.

Mid Controls:

The Active Mid control cuts mid frequencies.

Low Control:

This control adjusts the low spectrum of the amp. It's a boost cut style circuit.

The tone stack is a modified James style stack.

Reverb level control: The reverb control sets the reverb level of the amp.

Accent control: The accent trimmer (often called presence) sets the highs into the power amp. It can be used to brighten a dull speaker or make up for a dull room acoustic. This is a boost-only circuit, so zero means NO highs added to signal.

Depth control: The depth trimmer sets the lows into the power amp. It can be fill in the low end of a lean speaker or to warm up your overall low end. This is a boost-only circuit, so zero means NO lows added to signal.

Overdrive controls: Overdrive In control adjusts how much overdrive you get. Note that the input gain control sets the clean volume of the amp (also controlled by the master volume), but it also controls the signal into the overdrive. am. Overdrive Out, sets the overdrive level (relative to the clean channel, often called the ratio control), and the overdrive tone control is a high cut control on the overdrive channel only, which allows matching the tonalities between the clean and dirty channels.

©© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs ODH Amp manual Rev. 1.0 01-2024-AMF

Internal tube limiter: The amp features a preset, internal tube limiter which uses a 6AL5 tube as a limiter, whose threshold is set to limit the input to the ICE power module. This ensures a tube type overdrive, rather than the aggressive overdrive of digital clipping. By running the master high, you do not engage this limiter at all. As the master is run lower, and the input channel levels (clean and dirty) are increased, you will begin to hear the effect of the tube limiter and can achieve a great tube overdrive at low levels. As you push the input levels up and master down, you get the feel of a true tube amp “holding back” against your playing and picking.

5 (A)-REAR Panel

AC power cord input:

Using the supplied power cord. Connect AC POWER IN on amplifier and to AC power source. Please confirm your line voltage matches that of the amplifier!!!

AC power Fuse:

This fuse protects the amplifier if any malfunction occurs. Use ONLY stock fuse rating as supplied by factory. If this fuse blows more than once, there may be an issue with the amp requiring service. There are internal factory NON FIELD REPLACEABLE fuses. If these fuses fail, return the amp for service.

Power On/OFF rocker switch: Turns AC power on and off. All models are universal AC configured, so the amp can be plugged-in anywhere in the world and automatically set the proper AC power input voltage.

6 Effects Loop: The front panel effects loop is a series only loop, designed for line level signals. Use quality shielded cables (audio cables not speaker wires) and use line level effects for optimal performance.

7 The Line output:

The DI output is an electronically buffered ¼” output feeding another amp, or a recording application. There are three switch positions which affect its operation: One side mutes the power amp, while the other side mutes the line out. The amp can be operated without a speaker, but muting the signal to the amp is suggested.

8 Footswitch jack (marked F/S): The dual LED footswitch we provide operates on a TRS (tip, ring sleeve) wire. The OD output control is for manual overdrive without the footswitch. When the amp is cold, the front panel LED is Red, showing the mute status as activated. After warm up the LED turns green, showing it is ready for play. When you switch channels the LED switches to blue in overdrive.

DISCLAIMER: There are exposed Internal dangerous high-voltages in this amplifier. Do not attempt to service, repair you are not qualified to do so. Please contact Fuchs Audio beforehand with questions in this regard. Fuchs Audio takes no responsibility or shall be held liable for any personal harm caused or damage to this amplifier as a result of unauthorized service, repair or internal adjustments made to this amplifier. Please note: The DI output should not be plugged into a mixer with phantom power. This may cause noise and/or damage to the DI output circuitry as well as pops and excess noise through your bass cabinet and the main PA system or recording..

Power specifications: ODH

- 300W at 1% THD+N, 4Ohm
- 360W at 0.1% THD+N 4Ohm • 380W at 10% THD+N, 4Ohm • 450W at 1% THD+N, 2.7Ohm



© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs Bass Amp manual Rev. 1.0 01-2024-AMF

8 Warranty Information

The Fuchs Audio Technology Warranty

Fuchs Audio Technology® guarantees our products to be free from defective workmanship or material failure for a period of three years from date of new purchase to the original purchaser. This does not apply to Fuchs amplifiers that have been tampered with, damaged by shipping carriers, reverse engineered, or modified. This warranty is void if the amplifier is used with power attenuator type devices (Power Soaks, Air Brakes, Hot Plates etc.). Your warranty form/information must be returned to Fuchs Audio Technology® within 30 days of purchase, or your warranty will not be in effect.

Fuchs Audio Technology® reserves the right to suspend or terminate the above warranty at our sole discretion, should damage from any of the above limitations and or exclusions be detected upon examination.

Keep the information on this page for your records.
Please mail-in warranty form on next page

FUCHS MODEL _____

SERIAL NUMBER _____

Fuchs Audio Technology ® 407 Getty Ave, Clifton NJ, 07015
(973)-772-4220 www.fuchsaudiotechnology.com info@fuchsaudiotechnology.com

®© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs Bass Amp manual Rev. 1.0 01-2024-AMF

WARRANTY REGISTRATION FORM

This completed form must be returned to Fuchs Audio Technology within 30 days of purchase along with a copy of your receipt from your authorized dealer.

Please fill in all requested information on this form so we may register you for future warranty repairs or future upgrades, should they become available.

Purchasers Name _____

Address _____

City _____ State _____ Zip _____ Country _____

Phone Number _____

E-Mail address _____

Model _____

Serial Number _____

Date of Purchase _____

Dealer Name _____

Comments:

Please return this form to:

Fuchs Audio Technology®
(973) 772-4420

www.fuchsaudiotechnology.com

407 Getty Avenue, Clifton NJ, 07015

info@fuchsaudiotechnology.com

®© 2024 Fuchs Audio Technology. All rights reserved.

Fuchs Bass Amp manual Rev. 1.0 01-2024-AMF