CARE AND MAINTENANCE

Your Mackie subwoofer will provide many years of reliable service if you follow these guidelines:



Avoid exposing the subwoofer to moisture. If your loudspeakers are set up outdoors, be sure they are under cover if you expect rain.

- Avoid exposure to extreme cold (below freezing temperatures). If you must operate the subwoofers in a cold environment, warm up the voice coil slowly by sending a low-level signal through it for about 15 minutes prior to high-power operation.
- Use a slighty damp cloth with a mild soap solution to clean the cabinets. Only do this when the power is turned off. Avoid getting moisture into any of the openings of the cabinet, particularly where the driver is located.

S218s SPECIFICATIONS

Acoustic Performance

Frequency Range (-10 dB)

Sensitivity (1W/1m) 99 dB SPL
Max SPL long-term 122 dB @ 1m
Max SPL peak 128 dB @ 1m
Crossover Point 180 Hz, 12 dB/octave
Woofer Loading Bass reflex

Input/Output

Input/Output Type Neutrik SpeakonTM and

female 1/4-in. TS jack

Input Impedance (nominal)

8 ohms

Input Impedance (minimum)

3.9 ohms @ 110 Hz

Recommended Lowpass Filter (if using external

crossover) 150 Hz, 24 dB/octave

Recommended Amplifier Power

500 watts rms continuous 2000 watts peak

Low-Frequency Section

Woofer Diameter 18.0 in/457 mm Voice Coil Diameter 3 in/76 mm Diaphragm Material Cellulose Magnet Material Ferrite

Construction Features

Basic Design Bass reflex

Material 15 mm multi-layered plywood

Finish Black paint Handles One on each side

Grille Perforated metal with weather-

resistant coating

Physical Properties

 Height
 30.0 in/76.2 cm

 Width
 21.0 in/53.3 cm

 Depth
 21.0 in/53.3 cm

 Weight
 81.5 lb/37.0 kg

 Mounting Methods
 Floor mount only.

The S218s cabinet has no rigging points and is not suitable for flying. *Never attempt to suspend the cabinet by its handles.*

Disclaimer

Since we are always striving to make our products better by incorporating new and improved materials, components, and manufacturing methods, we reserve the right to change these specifications at any time without notice.

"Mackie" and the "Running Man" figure are registered trademarks of LOUD Technologies Inc.

All other brand names mentioned are trademarks or registered trademarks of their respective holders, and are hereby acknowledged.

Need Help?


You can reach a technical support representative Monday through Friday from 7 AM to 5 PM PST at:

1-800-898-3211

After hours, visit www.mackie.com and click Support, or email us at: techmail@mackie.com



S218s Frequency Response On-Axis



S218s Dimensions

