

THS Series Speakers

Ideal for all small venue applications, the THS Series speakers offer amazing high-end performance in rugged, easy-to-transport enclosures that sound and look great. These speakers are perfect for all total front-of-house (FOH) live sound reinforcement applications (indoors or outdoors): clubs, small halls, churches, schools and large rehearsal rooms.

- Durable, roadworthy cabinet construction with Tolex covering, reinforced corners, and large built-in recessed carrying handles
- Wide-angle, short-throw high-frequency dispersion horns provide clean, accurate treble for optimum clarity
- Convenient Speakon™ and 1/4" (6.3mm) connectors for professional hook-ups
- Frequency response: THS-1512 (75Hz-21KHz), THS-1515 (65Hz-21KHz)
- Sensitivity (1W/1M): THS-1512 (102dB), THS-1515 (103dB)
- Dimensions (WHD): THS-1512 (26"x15"x17.3", 66 x 38.1 x 43.9 cm); THS-1515 (29.5"x17.3"x19.7", 74.9 x 43.9 x 50 cm)
- Weight: THS-1512 (55 lbs, 25 Kg), THS-1515 (67 lbs, 30.4 Kg)



THS-1512

Full-range, 2-way speaker with 12" woofer, conical 6" X 15" titanium horn and 320W peak program power rating



THS-1515

Full-range, 2-way speaker with 15" woofer, conical 6" X 15" titanium horn and 600W peak program power rating

M-Cab™ Speakers

Powerful 2-way speakers perfect for all small venue applications, the M-Cab Series™ delivers maximum versatility, state-of-the-art cabinet design, and superior performance and specs with ultra-clean transparent sound at ground breaking affordability.



MC-12

Full-range, 2-way speaker with 12" woofer, 7" X 12.5" titanium horn, 500W peak program power rating and mineral loaded polypropylene trapezoid speaker enclosure

MC-15

Full-range, 2-way speaker with 15" woofer, 7" X 14" titanium horn, 500W peak program power rating and mineral loaded polypropylene trapezoid speaker enclosure

- Durable yet lightweight molded high-impact mineral loaded polypropylene enclosures, designed to deflect bumps and scrapes, and perfectly balanced for ease of portability and set-up, built-in handles for carrying
- Ultimate flexible design enables either FOH main speaker or stage monitor use. Compact trapezoidal shape perfect for hanging in clusters (with dual built-in threaded brass inserts for eye bolts), single mounting on a speaker tripod stand (with built-in 35 mm base mount insert), or mounted on side with the detachable speaker brace mounts provided (for use as dual-angle floor wedge monitors)
- 12" LF (MC-12), 15" F (MC-15), 2.5" (6.3 cm) voice coil
- Low impedance compensated crossovers with full driver protection
- Wide-angle, short throw, high-frequency dispersion horns with 1.5" diameter precision titanium compression driver
- 50 Hz to 8 KHz linear response
- 500W peak program power rating
- 95dB (1W@1M) sensitivity
- Speakon™ and 1/4" input jacks
- Lightweight: MC-12 (44 lbs, 20 Kg), MC-15 (48 lbs, 21.8 Kg)
- Compact sizing for ease of portability: MC-12 (17" x 23" x 12.3", 43.2 x 58.4 x 31.2 cm); MC-15 (17.3" x 26.6" x 13.6", 43.9 x 67.6 x 34.5 cm)
- Optional padded zippered vinyl carrying case available

P-Cab™ Powered Speakers

With internal amplification, in addition to the premium features of the popular M-Cab™ Series, the P-Cab™ combines the convenience of an active speaker system with superior performance, state-of-the-art versatile design, and unprecedented affordability.

- Durable yet lightweight molded high-impact, mineral-loaded polypropylene enclosure, designed to deflect bumps and scrapes and perfectly balanced for ease of portability and set-up; built-in handles for carrying
- Ultimate flexible design—flyable, stackable, pole mountable, or can be used as a floor monitor when laid on its side with supplied brace mounts
- Internal bi-amplified power system delivers a total of 250W RMS (LF/200W RMS, HF/50W RMS) and provides high quality audio performance more efficiently than conventional power amplifiers with passive speakers
- Easy to use built-in mixer with selectable XLR balanced Mic/Line inputs and Mix output; treble, bass and volume controls; and Signal and Clip LED
- Fused IEC power cord jack and 115V(60Hz) / 230V(50Hz) Select switch.
- Full top-end speaker features, including low impedance electronically compensated crossover (1/36 octave, 1500Hz) with full driver protection (pre-circuit limiter), wide-angle, short throw, high-frequency dispersion horn (90°H x 60°V) with 1.5" diameter precision titanium compression driver, 40Hz to 20KHz frequency response (-10dB), high SPL output capability (125dB @1M), and ultra low distortion (<0.02%)
- Lightweight compact sizing for portability: 49.5 lbs (22.5 Kg), 17" x 23" x 12.3", 43.2 x 58.4 x 31.2 cm)
- Optional padded zippered vinyl carrying case available



PCS-12

Full-range, 2-way active 250W RMS bi-amplified speaker with 12" woofer, 7" X 12.5" titanium horn, and mineral loaded polypropylene trapezoid speaker enclosure

ProPower Series™ Speakers

Ruggedly built, exceptional sound, most affordably priced — the ProPower Series™ from Nady Audio delivers the best value available in small PA speakers.

- All horns with high compression piezo drivers
- Durable black carpet cover
- Heavy duty plastic protective corners
- Integrated recessed carrying handles (PS112/PS115/ PTS515) for easy handling
- Lightweight: PS112 (35 lbs, 15.9 Kg), PS115 (55 lbs, 25 Kg), PTS515 (37 lbs, 16.8 Kg), PFW12 (35 lbs, 15.9 Kg), and PSW1 5 (48 lbs, 21.8 Kg)
- Sized for easy portability: PS112 (17"x 11.75"x 22.75", 43.2 x 29.8 x 57.8 cm); PS115 (19.3"x 14.6" x 28.1", 49 x 37.1 x 71.4 cm); PTS515 (17.5" x 13.8"x 25.6", 44.4 x 35 x 65 cm); PFW12 (16.5"x 26"x 19.1", 41.9 x 66 x 48.5 cm); PSW15 (18"x16"x23", 45.7 x 40.6 x 58.4 cm)
- Sensitivity (1W/1M): 91.5dB-PS112/PS115/PTS515; 90dB-PFW12
- Binding post (banana jack) and two 1/4" (6.3 mm) jack inputs
- Base mount inserts for mounting on speaker stands (PS112, PS115, PTS515); PSW15 with speaker stand insert on top of cabinet



PS112

Full-range, 2-way speaker with 12" woofer, 5" X 15" horn, and 300W peak program power rating



PS115

Full-range, 2-way speaker with 15" woofer, 5" X 15" horn, and 500W peak program power rating



PTS515

Full-range, 2-way speaker with 12" woofer, 5" X 15" horn, 400W peak program power rating and trapezoid speaker enclosure



PSW15

15" subwoofer speaker with 2" voice coil, 50 oz. magnet, 20-500Hz response, and 600W peak program power rating



PFW12

2-way floor wedge monitor speaker with 12" woofer, 4" X 10".5" horn, and 400W peak program power rating

PAM-10F Speaker

Compact, powerful and packing a punch, the PAM-10F sets new performance standards for professional speakers — at a perfectly affordable price.



PAM-10F

Full-range, 8 ohms, 2-way speaker with 10" woofer, 3" X 7" horn with 1.75 piezo voice coil, and 120W peak program power rating — can be used either for F.O.H. applications or as a floor wedge monitor.

- Great sound and projection, perfect for all small venue applications
- Compact, lightweight yet rugged cabinets with durable Tolex covering, reinforced plastic protected corners, and recessed carrying handles for roadworthy reliability and easy portability [16.55lbs (7.51g), 10"W x 20"H x 15"L, (25.4 x 50.8 x 38.1 cm)]
- Base mount inserts for speaker stand mounting
- 92dB sensitivity (1W/1M)
- 1/4" jack inputs