

Yamaha Stagepas 600BT Portable PA System - Vocal Pack

Specifications:

Yamaha Stagepas 600BT Portable PA System

- **Speaker Type:** 2-way bass-reflex speakers
- **Frequency Range:** 55Hz - 20kHz (-10dB)
- **Nominal Coverage:** 90° x 60° (H x V)
- **LF Driver:** 10" / 25cm cone
- **HF Driver:** 1.4" / 3.56cm voice coil compression driver
- **Maximum Output Level:** 129dB SPL / speaker (1m; on axis)
- **Amplifier Maximum Output Power at 4 Ohms:**
 - **Dynamic:** 680W (340W + 340W)
 - **Continuous:** 560W (280W + 280W)
- **Channels:** 10
- **Input Channel Functions:**
 - Hi-Z switch (CH4)
 - ST/MONO switch (CH5/6 - 9/10)
- **Output Channel Functions:**
 - Feedback suppressor
 - 1-Knob Master EQ™
- **Inputs:** 4 mono mic / line + 6 mono / 3 stereo line
- **Phantom Power:** +30V (CH1, 2)
- **Outputs:**
 - Speakers OUT (L, R)
 - Monitor OUT (L/MONO, R)
 - Subwoofer OUT (MONO) with auto HPF
- **Bluetooth:** Bluetooth Ver.4.1, A2DP v1.2
- **Maximum Bluetooth Range:** Approx. 10-metres
- **Foot Switch Input:** For Reverb (foot switch not included)
- **EQ Bands:**
 - **High:** High shelving, 8kHz
 - **Mid:** Mid peaking, 2.5kHz
 - **Low:** Low shelving, 100Hz
- **DSP:** SPX digital reverb (4 program, parameter control)
- **Floor Monitor Angle:** 50°
- **Pole Socket:** 34.8mm - 35.2mm pole socket with StageLok™
- **Handles:** 1 x top (per speaker)
- **Power Requirements:** 100V - 240V, 50Hz/60Hz
- **Power Consumption:**
 - **Idle:** 35W
 - **1/8 Power:** 100W
- **Included Accessories:**
 - Cover panel
 - Power cord, 2-metres
 - 2 x Speaker cables, 6-metres
 - 12 x Non-skid pads
 - 2 x Ferrite cores
 - 2 x Cable ties
- **Dimensions:**
 - **Speaker:** 335mm x 545mm x 319mm (per speaker)
 - **Mixer:** 348mm x 197mm x 135mm
- **Weight:** 25.6kg (10.9kg per speaker, 3.8kg mixer)

beyerdynamic TG V35d s Dynamic Handheld Microphone with Switch

- **Mic Application:** Vocal (singing, speech)
- **Polar Pattern:** Supercardioid
- **Frequency Response:** 30Hz - 18kHz
- **Transducer Type:** Dynamic
- **Operating Principle:** Pressure gradient
- **Rear Attenuation at 1kHz:** Greater than 20dB at 140°
- **Open Circuit Voltage:** 2.5mV/Pa (-52dBV)
- **Nominal Impedance:** 600 Ohms
- **Load Impedance:** 2 k Ohms
- **Microphone Type:** Handheld
- **Transmission Type:** Wired
- **Connection:** 3-pin XLR, male
- **Length:** 186mm
- **Shaft Diameter:** 24/38mm
- **Head Diameter:** 50mm
- **Weight:** 305g
- **Product Code:** 707244

PA Speaker Stands (Pair) With Carry Bag

- **Colour:** Black
- **Material:** Aluminium
- **Dimensions:** W: 1000mm D: 1000mm
- **Height Adjustment:** 1200mm - 2000mm
- **Max Load:** 50kg
- **Top Hat:** 35mm

Boom Mic Stand by Gear4music

- **Mic Thread:** 5/8" (15.875mm)
- **Min Stand Height:** 900mm (floor to boom swivel)
- **Max Stand Height:** 1500mm (floor to boom swivel)
- **Stand with Full Extended Boom Height:** 970mm - 1515mm
- **Boom Arm Length:** 800mm