


NT5

FEATURES


- True condenser transducer
- Gold sputtered 1/2" Capsule
- Heavy duty satin-nickel-plated body
- Low noise
- Full frequency response
- Custom WS5 Wind Shield
- Custom RM5 Stand Mount
- Supplied as a MATCHED PAIR in a Custom Carry Case

interstage

Phistersvej 31, 2900 Hellerup, Danmark
Telefon 3946 0000, fax 3946 0040
www.interstage.dk
- pro audio with a smile



NT5 Frequency Response



NT5 Polar Response

NT5 Specifications:

Acoustic Principle:	Externally polarised 0.5" (13mm) condenser transducer
Active Electronics:	J-FET Impedance converter with bipolar output buffer
Pickup Pattern:	Cardioid (see graph)
Frequency Response:	20Hz to 20kHz (see graph)
Output Impedance:	200Ω
Sensitivity:	-38 dB re 1v/Pa (12mV @ 94dB SPL)+/-2dB
Equivalent Noise:	<16 dBA SPL (per IEC651, IEC268-15)
Maximum Output:	+13.9 dBu (@ 1% THD into 1kΩ)
Dynamic Range:	>128 dB (per IEC651, IEC268-15)
Maximum SPL:	143 dB (@ 1% THD into 1kΩ)
Signal/Noise:	78 dB (1kHz rel 1 Pa; per IEC651, IEC268-15)
Power Requirements:	P48, P24 phantom
Packed Weight:	1.8kg (Mic only 100g)
Mic Dimensions:	Diameter: 20mm Length: 118mm
Packed Dimensions:	310 x 300 x 110mm