

QSC K12.2 12" Active PA Speaker - Specifications

- **Configuration:** Multi-purpose 2-way powered loudspeaker
- **Frequency Range:** 45Hz - 20kHz (-10dB)
- **Frequency Response:** 50Hz - 20kHz (-6dB)
- **Nominal Coverage Angle:** 75° Axisymmetric
- **Maximum SPL:**
 - **Peak:** 132dB at 1M
 - **Continuous:** 126dB at 1M
- **LF Transducer:** 12" (305mm) cone
- **HF Transducer:** 1.4" (35.6mm) titanium diaphragm compression driver
- **Amplifier:** Class D
 - **Peak Power:** 1800W (LF), 225W (HF)
 - **Cooling:** Low-noise variable-speed fan
- **Controls:**
 - Power
 - 3 x Level
 - Rotary push encoder
 - 2 x Selection buttons
- **Indicators:**
 - Monochrome LCD Display, 1.75" x 1" (45mm x 25.4mm)
 - 2 x Power LED (front and rear)
 - 3 x Input signal LED
 - Input A Mic selected LED
 - Input B Hi-Z selected LED
 - Limiter active LED
- **Connectors:**
 - 2 x Locking XLR-1/4" combo (Mic/Line input and Hi-Z/Line input)
 - 1 x 3.5mm TRS (Stereo input)
 - 2 x XLR/M (Loop-thru output)
 - 1 x XLR/M (Mix output)
 - 1 x Locking IEC power connector
- **Enclosure:**
 - **Material:** Impact-resistant ABS
 - **Attachment Points:** 2 x M10 threaded inserts plus Pull-Back
 - **Colour:** Black (RAL 9011)
 - **Grille:** 18-gauge powder-coated steel with internal cloth lining
- **Regulatory:**
 - CE
 - WEEE
 - UL
 - China RoHS
 - RoHS II
 - FCC Class B
- **AC Power Input:** Universal power supply, 100-240VAC, 50-60Hz
- **AC Power Consumption:** *1/8th power*
 - **100VAC:** 2.1A
 - **120VAC:** 1.9A
 - **240VAC:** 1.1A
- **AC Power Consumption on Standby:** 0.2A at any voltage
- **Dimensions:** 602mm x 356mm x 350mm / 23.7" x 14" x 13.8" (H x W x D)
- **Weight:** 17.7kg / 39lbs

QSC KS212C Cardioid Subwoofer - Specifications

- **Configuration:** Dual 6th-Order Bandpass Cardioid Subwoofer
- **LF Transducer:** 2 x 12", Cone
- **Frequency Response (-6 dB):** 44Hz - 104Hz
- **Frequency Response (-10 dB):** 39Hz - 118Hz
- **Nominal Coverage Angle:** 180° Cardioid (15 dB Rear Rejection @ 70Hz)
- **Maximum Rated SPL:** 132 dB @ 1m, Peak
- **Amplifier:** Class D, 2 x 1800W (Peak)
- **Cooling:** Low-Noise, Variable Speed Fan
- **Controls:** Power, Gain, Rotary Encoder, 2 x Selection Buttons
- **Indicators:** 2 x Power LED (Front and Rear), Input Signal LED, Limiter Active LED
- **Connectors:** 2 x Locking XLR/F 1/4" Combo
- **Enclosure:** 18mm Birch Plywood
- **Colour:** Black
- **Grille:** Internal Woofer Cover
- **AC Power Input:** Universal Power Supply 100 - 240V, 50/60Hz
- **AC Power Consumption:** 1/8th Power
- **Weight:** 40.1 kg
- **Dimensions**
 - **Height:** 610 mm
 - **Width:** 381 mm
 - **Depth:** 498 mm