


Technical Specifications

Version 1.1 September 2002



EUROSTACK

Ultra low-noise design 18-input 3/2-bus mic/line mixer with premium mic preamplifiers and 24-bit multi-FX processor

- ▲ Ultra low-noise ULN design, highest possible headroom, ultra-transparent audio
- ▲ 6 new state-of-the-art, studio-grade IMP “Invisible” Mic Preamps with:
 - 130 dB dynamic range for 24-bit, 192 kHz sampling rate inputs
 - Ultra-wide 60 dB gain range
 - Lowest possible distortion 0.0007% (20 Hz - 20 kHz)
- ▲ Integrated 24-bit digital stereo FX processor with 99 great-sounding VIRTUALIZER presets including reverb, delay, chorus, compressor, tube distortion, vinylizer and more plus 1 kHz test tone generator
- ▲ Breathtaking 3D stereo surround effect for more vitality and enhanced stereo image
- ▲ 9-band stereo graphic EQ allows precise frequency correction of monitor or main mixes
- ▲ Effective, extremely musical 3-band EQ with semi-parametric mid band plus switchable low-cut filter on all mono channels
- ▲ Inserts on each mono channel for flexible connection of outboard equipment
- ▲ 14 balanced high-headroom line inputs with +4/-10 level selection on stereo channels
- ▲ State-of-the-art 4580 operational amplifiers provide lowest noise and distortion—better than 4560 op amps
- ▲ 3 aux sends per channel: 1 pre fader for monitoring, 1 pre/post fader switchable for monitoring/FX applications, 1 post fader (for internal FX or as external send)
- ▲ Peak LEDs, mute, main mix and subgroup routing switches, solo and PFL functions on all channels
- ▲ 2 subgroups with separate outputs for added routing flexibility
- ▲ 2 multi-functional stereo aux returns with flexible routing
- ▲ Balanced main mix outputs with TRS and gold-plated XLR connectors, separate control room, headphones and stereo tape outputs
- ▲ Control room/phones outputs with multi-input source matrix
- ▲ Tape inputs assignable to main mix or control room/phones outputs
- ▲ Switchable +48 V phantom power for condenser microphones
- ▲ Long-wearing 60 mm logarithmic-taper ALPS® faders and sealed rotary controls
- ▲ Internal switch-mode power supply for maximum flexibility (100 - 240 V~), noise-free audio, superior transient response plus lowest possible power consumption for energy saving
- ▲ Extremely rugged steel construction ensures long life even under the most demanding conditions
- ▲ Rack mount brackets included
- ▲ Manufactured under ISO9000 certified management system

EUROSTACK UB1832FX-PRO

SPECIFICATIONS

Microphone inputs (IMP Invisible Mic Preamp)

Type	XLR, electronically balanced, discrete input circuit
Mic E.I.N. (20 Hz - 20 kHz)	
@ 0 Ω source resistance	-134 dB / 135.7 dB A-weighted
@ 50 Ω source resistance	-131 dB / 133.3 dB A-weighted
@ 150 Ω source resistance	-129 dB / 130.5 dB A-weighted

Frequency response	<10 Hz - 150 kHz (-1 dB), <10 Hz - 200 kHz (-3 dB)
--------------------	---

Gain range	+10 to +60 dB
Max. input level	+12 dBu @ +10 dB Gain
Impedance	approx. 2.6 k Ω balanced
Signal-to-noise ratio	110 dB / 112 dB A-weighted (0 dBu In @ +22 dB gain)

Distortion (THD+N)	0.005% / 0.004% A-weighted
---------------------------	----------------------------

Line input

Type	1/4" TRS connector electronically balanced
Impedance	approx. 20 k Ω balanced 10 k Ω unbalanced
Gain range	-10 to +40 dB
Max. input level	30 dBu

Fade-out attenuation¹ (Crosstalk attenuation)

Main fader closed	90 dB
Channel muted	89 dB
Channel fader closed	89 dB

Frequency response

Microphone input to main out	
<10 Hz - 90 kHz	+0 dB / -1 dB
<10 Hz - 160 kHz	+0 dB / -3 dB

Stereo inputs

Type	1/4" TRS connector, electronically balanced
Impedance	approx. 20 k Ω
Max. input level	+22 dBu

EQ mono channels

Low	80 Hz / ± 15 dB
Mid	100 Hz - 8 kHz / ± 15 dB
High	12 kHz / ± 15 dB

EQ stereo channels

Low	80 Hz / ± 15 dB
Low Mid	500 Hz / ± 15 dB
High Mid	3 kHz / ± 15 dB
High	12 kHz / ± 15 dB

Aux sends

Type	1/4" TS connector, unbalanced
Impedance	approx. 120 Ω
Max. output level	+22 dBu

Stereo aux returns

Type	1/4" TRS connector, electronically balanced
Impedance	approx. 20 k Ω bal. / 10 k Ω unbal.
Max. input level	+22 dBu

Main outputs

Type	XLR, electronically balanced and 1/4" TRS balanced
Impedance	approx. 240 Ω balanced / 120 Ω unbalanced
Max. output level	+28 dBu

Control room outputs

Type	1/4" TS connector unbalanced
Impedance	approx. 120 Ω
Max. output level	+22 dBu

Headphones outputs

Type	1/4" TRS connector, unbalanced
Max. output level	+19 dBu / 150 Ω (+25 dBm)

DSP

Converter	24-bit Texas Instruments™ 24-bit Sigma-Delta, 64/128-times oversampling
Sampling rate	46,875 kHz

Main mix system data²

Noise	
Main mix @ - ∞ , Channel fader - ∞	-101 dB
Main mix @ 0 dB, Channel fader - ∞	-93 dB
Main mix @ 0 dB, Channel fader @ 0 dB	-81 dB

Power supply

Power consumption	43 W
Fuse	100 - 240 V ~: T 1.6 A H
Mains connection	Standard IEC receptacle

Physical/weight

Dimensions (H x W x D)	approx. 3 7/8" (97 mm) x 16 1/16" (408 mm) x 14 1/16" (367 mm)
Weight (net)	approx. 4.7 kg

Measuring conditions:

- 1 kHz rel. to 0 dBu; 20 Hz - 20 kHz; line input, main output; unity gain.
- 20 Hz - 20 kHz; measured at main output. Channels 1 - 4 unity gain; EQ flat; all channels on main mix; channels 1/3 as far left as possible, channels 2/4 as far right as possible. Reference = +6 dBu.

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

EURORACK UB1832FX-PRO

The information contained in this manual is subject to change without notice. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER, EURORACK, VIRTUALIZER, POWERPLAY and ULTRALINK are registered trademarks. ALL RIGHTS RESERVED.

TEXAS INSTRUMENTS™ is a registered trademark of Texas Instruments Incorporated,
which is in no way associated or affiliated with BEHRINGER. © 2002 BEHRINGER Spezielle Studiotechnik GmbH.
BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany
Tel. +49 (0) 21 54 / 92 06-0, Fax +49 (0) 21 54 / 92 06-30
