



# COLORado™ Batten 72 Tour

## SPECIFICATIONS & FEATURES

CHAUVET®



### AT A GLANCE:

*RGBWA Color Mixing*



### Key Features:

- RGBWA Color Mixing
- PowerCon™ Connectors
- Direct 3 & 5-Pin DMX Connections
- 5 Distinct Dimming Curves
- Color temperature presets

### About this light:

The COLORado™ Batten 72 Tour is a 3, 4, 5, 6, 7, 9, 13 or 15-channel LED linear wash. The luminaire features RGBWA color mixing from 72 1 W red, green, blue, white and amber LEDs.

Perfectly suited for touring or installation the COLORado™ Batten 72 Tour is the direct result of listening to customers wants and needs.

The COLORado™ Batten 72 Tour features PowerCon™ connectors for power in and out as well as direct 3 and 5 pin DMX connections. The linear fixture is broken into controllable sections or controllable as a whole. Also added are white and amber LEDs for more vibrant colors and more precise color temperature. 5 selectable dimming curves were added to mimic those of conventional lighting sources and insure consistent fade out cues. Like all COLORado™ fixtures, the COLORado™ Batten 72 Tour is also flicker free and safe for video use.

### DETAILED SPECIFICATIONS:

#### FEATURES

- DMX channels: 3, 4, 5, 6, 7, 9, 13, or 15
- Five distinct dimming curves
- Additional power output: max 6 units @ 120 V
- LED display with lock-out feature
- NEUTRIK® PowerCon™ power input and output connector
- 3-pin and 5-pin DMX input and output connectors
- Adjustable feet double as hanging bracket
- Color calibration

#### SPECIFICATIONS

- DMX connectors: 3-pin & 5-pin
- Source: 72 (1 W) LEDs, 50,000 hours
- Configuration: 18 red (350 mA), 18 green (350 mA), 18 blue (350 mA), 9 white (350 mA), 9 amber (350 mA)
- Installed Optic(s): 30°
- Beam angle: 30°
- Field angle: 39.6°
- Lux: 669 @ 5 m
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 120 V, 60 Hz: 87 W, 1.43 A (operating)
- Power Consumption 230 V, 50 Hz: 87 W, 0.78 A (operating)
- Power linking: 6 units @ 120 V / 11 units @ 230 V
- Dimensions: 2.9 x 38.9 x 6.1 in (74 x 989 x 156 mm)
- Weight: 9.8 lbs (4.4 kg)
- Power Connection: Neutrik® powerCON® power input and output connector
- Control Connection: 3-pin and 5-pin DMX input and output connectors
- Certification: CE, ETLc
- Environment: IP20, dry location

[www.chauvetlighting.com](http://www.chauvetlighting.com)  
[www.chauvetlighting.co.uk](http://www.chauvetlighting.co.uk)

CHAUVET®