

SR 40 diversity



Digital Four Level Diversity system for interference - free reception Rugged metal case Full metering for easy status monitoring Professional XLR and 1/4" outputs

The SR 40 diversity is a stationary receiver for all WMS 40 and microtools Series transmitters. Operating in the 710 MHz to 865 MHz UHF range, the SR 40 diversity is perfectly suited for small stages, clubs, small touring systems, places of worship, hotels, gyms, etc. The plug and play concept and fixed preset frequency let you set up and operate the system quickly and efficiently even if you are not a trained sound engineer. Professional outputs include a balanced XLR and unbalanced TS 1/4" jack for connecting to every kind of equipment. An output level control allows you to match the SR 40 diversity's output signal to the input stage of the subsequent device. The rugged half - rack case gives you the choice of using the receiver free - standing or mounting it in a 19" rack.

Technical specifications

Carrier frequency range	710 MHz to 865 MHz
Modulation	FM
Audio bandwidth	40 to 20,000 Hz
THD	0.8% typ.
Signal/noise ratio	103 dB (A) typ.
Power supply	120/230 V AC, 50/60 Hz, 95 15 mA
Audio outputs	balanced XLR and unbalanced TS 1/4" jack, adjustable from mic to line level, 2 V rms max.
Dimensions	200 x 135 x 42 mm / 7.8 x 5.3 x 1.6 in.
Net weight	470 g / 16.6 oz.
Accessories (included)	Power supply