

**Frequency range (-10 dB, half space):**

49 Hz to 21 kHz

**Sensitivity (1 Watt/1 meter):**

97 dB

**Power rating (program):**

400 Watts

**Power capacity (peak):**

800 Watts

**Transducer complement:**

Heavy duty 15" woofer with 2 3/8" voice coil and 50 oz. magnet, 14XT™ 1.4" titanium diaphragm dynamic compression driver

**Driver protection:**

Positive temperature coefficient resistor

**Nominal coverage pattern:**

90° x 40°

**Nominal impedance:**

8 Ohms

**Input connections:**

Two 1/4" phone jacks in parallel

**Enclosure materials and finish:**

Injection-molded 1/4" thick polypropylene with textured finish; dark gray color

**Dimensions (H x W x D):**

28.562" x 21.312" x 17"

72.55 cm x 54.13 cm x 43.18 cm

Width in rear: 11.5" {29.21 cm}

**Weight:**

42 lbs. (19.1 kg)

**Mounting or suspension:**

- ▲ Molded-in stand-mounting cup, top and bottom flying point inserts

**Bullets:**

- Two-way sound reinforcement enclosure
- 15" heavy-duty woofer with 2 3/8" voice coil and 50 oz. magnet
- 14XT™ titanium diaphragm compression driver with 1.4" titanium diaphragm
- 400 Watts program/800 Watts peak power handling
- Crossover network for driver protection and EQ
- High frequency driver protection
- 90° x 40° coverage constant-directivity horn for better off-axis tonality
- Lightweight trapezoidal enclosure



## SPECIFICATIONS PR™ 15

- Durable plastic injection-molded enclosure
- Heavy duty steel grille
- Molded-in pole mount
- Top and bottom flying point inserts

### Description

The PR 15 is a two-way sound reinforcement system consisting of a heavy duty 15" woofer and a 14XT™ titanium diaphragm, dynamic compression driver mounted on a 90° x 40° coverage constant-directivity horn.

The lightweight-yet-rugged injection-molded plastic enclosure with molded-in stand-mount cup facilitates portable use for live music or speech sound. A black powder-coated steel grille provides driver protection and a professional appearance.

The PR 15 speaker system is rated at 400 Watts program power handling, and the full crossover network includes high voltage film capacitors and high frequency driver protection for clear, punchy sound and excellent long-term reliability. Two 1/4" phone jack input connectors make daisy-chaining to other speakers simple.

**⚠ Caution:** Before attempting to suspend the PR 15 consult a certified structural engineer. The speaker may fall due to improper suspension, resulting in serious injury and property damage. Additional speaker enclosures must not be suspended below a PR 15, nor should additional weight be

suspended from one of these units. Use only the correct mating hardware. All associated rigging is the responsibility of others.

Always use all four inserts of a given group as a set. NEVER use just one insert to fly a cabinet! The four insert groupings include a top group and a bottom group, but some models have an additional group of four on the rear plane of the cabinet. Maximum enclosure angle from vertical hang: 30°

When mounting or flying, you must use a suitable safety chain or wire rope to secure the speaker loop this through the top handle and firmly attach to a suitable structural member as indicated by a certified structural engineer.

The recommended range of torque for the mounting bolt is 3 to 3-3/4 lb./feet of torque. DO NOT OVERTIGHTEN! If an insert spins, it has been damaged and the cabinet cannot be flown!

Never transport the cabinet while mounted on an array bracket, or other mounting bracket, this may unduly stress the mounting inserts.

### **WARNING! (note to structural engineer)**

The end of the mounting bolt should not penetrate the cabinet more than 1/2" beyond its surface.

If this penetration depth is exceeded, then the insert may be damaged or unseated from the cabinet, severely compromising its the mounting integrity!

The correct mounting bolt diameter and threads per inch are: 1/4" x 20. We recommend the use of a grade 5 bolt. For custom brackets, we recommend a 5/16" hole for the bolts to allow for tolerances and adjustment.

### **3 + 2 YEAR LIMITED WARRANTY**

**NOTE:** For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box 2898, Meridian, Mississippi 39301-2898.

PR 15 Input Plate

**PR 15**




DESIGNED AND MADE IN U.S.A.

**MAX POWER: 400W PROGRAM**

IMPEDANCE: 8 OHMS

WARNING: THIS SPEAKER SYSTEM CAN PERMANENTLY DAMAGE HEARING! USE EXTREME CARE SETTING MAXIMUM LOUDNESS

HF DRIVER PROTECTION



FULL RANGE INPUTS  
IN PARALLEL



**DANGER**

BEFORE ATTEMPTING TO SUSPEND THIS SPEAKER CONSULT A CERTIFIED STRUCTURAL ENGINEER. SPEAKER CAN FALL FROM IMPROPER SUSPENSION, RESULTING IN SERIOUS INJURY AND PROPERTY DAMAGE. DO NOT SUSPEND OR MOUNT ANY OTHER PRODUCT OR DEVICE FROM THIS ENCLOSURE! USE ONLY GRADE 5 HARDWARE OR BETTER.

# SPECIFICATIONS PR™ 15



80304975

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 711 A Street • Meridian • MS • 39301 • (601) 483-5365 • FAX (601) 486-1278 • [www.peavey.com](http://www.peavey.com)  
©2003 Printed in the U.S.A. 11/03

