





CVXL SERIES POWERED LOUDSPEAKERS

Selecting a powered speaker solution should never be a compromise. The Cerwin Vega CV Series speaker line delivers best in class design whether your audio needs are small, medium or large coverage applications. The CVXL line of five powered speakers single 12", 15" and dual 15" tops with single 18" and dual 18" subwoofers power their way through medium to large venues. As a fully integrated solution, the 1500 Watt Class D amplifier (2000 Watts for Subwoofers) runs cool and stays clean, even in the most demanding environments. Engineered to deliver clarity, rich bass, wide dispersion, and accuracy all the way to the back rows—year after year—the CVXL line is ideal for Houses of Worship, large venues, hotels and resorts, theaters and outdoor concerts applications. The modern, professional look of Cerwin Vega's exclusive new Tour Shield finish is the perfect fit for demanding tours and rentals. When power, ruggedness, and accuracy aren't optional but essential, you can trust the CVXL line—the culmination of Cerwin Vega's 65 years of delivering professional live sound solutions.

KEY BENEFITS

- 1500 Watts Class D Power with 2000 Class D Power for Subwoofers
- 3 Channel Mixer with 2 Combo XLR/TRS Inputs, 1 TS Stereo Input & 3 XLR Outputs
- Main/Monitor and Live/Playback EQ Modes
- Cerwin Vega Proprietary Tour Shield™ Finish
- Cardioid Mode











| | CVXL-112* | CVXL-115* | CVXL-215* | CVXL-118s* | CVXL-218s* |
|---------------------------------|--|--|--|--|--|
| Power Rating | 1500 | 2000 | 2000 | 2000 | 2000 |
| Amplifier Class | D | D | D | D | D |
| Frequency Response (+/- 3dB) | 55Hz - 18kHz | 50Hz - 18kHz | 47Hz - 18kHz | 35Hz - 225Hz | 33Hz - 225Hz |
| Frequency Range (+/- 10dB) | 50Hz - 20kHz | 45Hz - 20kHz | 42 Hz - 20kHz | 30Hz - 250Hz | 28Hz - 250Hz |
| Max SPL | 135 | 135 | 137 | 137 | 140 |
| HF Driver | 1.75" | 1.75" | 1.75" | N/A | N/A |
| LF Driver | 12" | 15" | Dual 15" | 18" | Dual 18" |
| Dispersion | 90° x 60° | 90° x 60° | 90° x 60° | N/A | N/A |
| Input/Output | (2) Combo XLR/TRS Inputs (1) TS Pair Input (3) XLR Outputs | (2) Combo XLR/TRS Inputs (1) TS Pair Input (3) XLR Outputs | (2) Combo XLR/TRS Inputs (1) TS Pair Input (3) XLR Outputs | (2) Combo XLR/TRS Inputs N/A (3) XLR Outputs | (2) Combo XLR/TRS Inputs N/A (3) XLR Outputs |
| Switches | Main/Monitor Mode Live/Playback EQ High Pass Filter | Main/Voice Mode Live/Playback EQ High Pass Filter | Main/Voice Mode Live/Playback EQ High Pass Filter | Polarity Cardioid Mode Crossover Frequency | Polarity Cardioid Mode Crossover Frequency |
| Enclosure | Wood | Wood | Wood | Wood | Wood |
| Finish | TourShield | TourShield | TourShield | TourShield | TourShield |
| Dimensions (h x w x d) | 648mm x 400mm x 405mm | 721mm x 460mm x 493mm | 1128mm x 460mm x 493mm | 621mm x 535mm x 649mm | 621mm x 1050mm x 649mm |
| Weight (lbs) | 63 | 75 | 120 | 100 | 155 |

