

LED TECHNO STROBE™



CONTROL FEATURES

- 3-channel DMX-512 LED white strobe light
- Blackout/static/dimmer/strobe
- Adjustable flash rate, dimmer and static in stand-alone via dipswitches
- Built-in automated programs via master/slave or DMX
- Built-in sound activated programs via master/slave or DMX

ADDITIONAL FEATURES

- Compatible with CHAUVET® Satellite™ system
- Linkable with LED Shadow™, LED Shadow™ 2, LED Techno Strobe™, LED Techno Strobe™ RGB, LEDsplash™ 200B and LEDsplash™ 2 in stand alone
- Additional power output: max 50 units @ 120V (see manual for details)
- Includes brackets for wall and truss mounting

SPECIFICATIONS

- Beam angle: 21° x 24°
- Field angle: 40° x 43°
- Lux: 1,321 @ 1m
- Light source: 192 (white) LEDs 100,000hrs
- Color temperature: 6,500K - 8,000K
- Power and current: 120V, 60Hz: 0.1A operating, 0.2A inrush
- AC power: Autoswitching 100V - 240V 50/60Hz
- Weight: 4.9lbs (2.2kg)
- Size: 14in x 9.75in x 6.5in
356mm x 248mm x 165mm

www.chauvetlighting.com

info@chauvetlighting.com

t: 954.929.1115

3000 North 29th Court

Hollywood, FL 33020


CHAUVET®
Value • Innovation • Performance